




Baryval

HORMIGONERAS - TRUCK MIXERS - BÉTONNIÈRES
4 - 6 - 7 - 8 - 9 - 10 m³ / cbm.



SERVIPLEM, S. A.





HORMIGONERAS
TRUCK MIXERS
BÉTONNIÈRES

Baryval

CARACTERÍSTICAS TÉCNICAS • TECHNICAL CHARACTERISTICS • CARACTERISTIQUES TECHNIQUES

Modelo: AMN	4/101	4/111	6/101	6/111	6,5/101	6,5/111	7/101	7/111	8/101	8/111	9/101	9/111	10/101	10/111
Volumen nominal (m ³)	4	4	6	6	6,5	6,5	7	7	8	8	9	9	10	10
Volumen geométrico (l.)	7884	7884	10060	10060	10520	10520	11950	11950	11950	11950	14970	14970	16250	16250
Capacidad efectiva (%)	50,74	50,74	59,64	59,64	61,78	61,78	58,57	58,57	66,94	66,94	60,12	60,12	61,54	61,54
Torna	motor vehiculo													
de fuerza	SI													
Velocidad tambor (r.p.m.)	-													
① Capacidad depósito de agua (l.)	-													
② Caudal bomba de agua (l/min)	625													
③ Presión depósito de agua (kg/cm ²)	-													
④ Peso (kg)	-													
Diámetro max. tambor (Ød)	2598	2875	3200	3550	3250	3600	3400	3750	3400	3830	3800	4260	4000	4460
Ángulo de inclinación tambor (β)	15	15	15	15	15	15	15	15	15	15	12	12	12	12
Distancia entre soportes (s)	3040	3040	3603	3603	3719	3719	4086	4086	4086	4086	4846	4846	5149	5149
Distancia a soporte motor aux. (s')	-													
Anchura máxima (a)	-													
Altura a tova de carga (h)	2398	2398	2538	2538	2569	2569	2667	2667	2667	2667	2701	2701	2765	2765
Altura total (H)	2398	2398	2538	2538	2569	2569	2667	2667	2667	2667	2720	2720	2785	2785
Voladizo (v)	-													
Longitud total (L)	4830	-	5387	-	5503	-	5873	-	5873	-	6466	-	6831	-
Longitud total con motor aux. (L')	-	4865	-	5427	-	5543	-	5910	-	6413	-	7252	-	7556

NOTA: SERVIPLEM BARYVAL se reserva el derecho de hacer modificaciones sin previo aviso • NOTE: SERVIPLEM BARYVAL reserves the right to make modifications without prior notice • NOTE: SERVIPLEM BARYVAL se réserve le droit de faire des modifications sans préavis



Tambor de amasado y hélices, construido en acero BARYHARD-355, altamente resistente al desgaste.

Protección complementaria antidesgaste, en la parte superior de las hélices.

Mixing drum and blades, built in steel BARYHARD-355, extraordinarily long lasting against wearing.

The mixing blades have a protective strip welded along the top part.

Cuve de malaxage avec double jeu de spires, construite en acier spécial antiusure BARYHARD-355.

Protection complémentaire antiusure dans la partie supérieure des spires.

Tolvas y canales construidos en chapa de acero BARYHARD-355, altamente resistente al desgaste.

Hoppers and chutes built in BARYHARD-355 steel plate, extraordinarily long-lasting against wearing.

Trémies et goulottes en acier spécial antiusure BARYHARD-355.



Reductores de engranajes con opción SAUER y ZF.

Vista del refrigerador de aceite.

Planetary gear reducer, optionally SAUER or ZF.

Oil cooler view.

Réducteur de marque SAUER ou ZF.

Vue du refroidisseur d'huile.



Bomba y motor hidráulicos con opción SAUER, EATON o REXROTH.

Hydraulic pump and motor, optionally SAUER, EATON or REXROTH.

Pompe et moteur hydrauliques marque SAUER, EATON ou REXROTH.



Cabina de granallado donde se tratan todas las piezas de acero, aplicando posteriormente una capa de pintura antioxidante y acabado final con pintura en poliuretano.

Shotblasting cabin where all the steel components are treated. Later covered with antioxidant primer and finished with polyurethane layer.

Cabine de granallé où on traite toutes les pièces en acier. On applique de la peinture antioxydante en apprêt, et la finition en peinture polyurethane.

SERVIPLEM, S. A.

Polygono Malpica, calle D. nº 67 50016 ZARAGOZA (SPAIN)
Hormigoneras: Tel. +34 976 46 53 40 - Fax +34 976 57 41 74
Cisternas: Tel. +34 976 58 81 65 - Fax +34 976 57 34 79
E-MAIL: baryval@serviplem.com

NOTA: El Certificado de Registro de empresa se refiere a las hormigoneras sobre camión fabricadas en Zaragoza. - The Quality Certificate is for the truck concrete-mixers manufactured in Zaragoza. - Le Certificat de Qualité fait allusion aux bétonnières sur camion fabriqués à Zaragoza.